



# Vine Trimmer Type DE

A lane and 'walking stick-shaped' device

On the Type DE, the bolted cutting units with 3mm shell also ensure the greatest stability. The Type DE vine trimmer also features individually adjustable side cutting units with separate collision protection devices, frame with hydraulic lateral tilt, single-acting height adjustments and common cutting unit width adjustment.



For further information visit [www.freilauber.de](http://www.freilauber.de),  
[www.provideag.ca](http://www.provideag.ca) or scan the QR-Code.

1.800.263.1287  
905.563.8261  
Beamsville, On, Canada

**PROVIDE AGRO**  
A BARTLETT COMPANY ESTABLISHED 1912

[info@provideag.ca](mailto:info@provideag.ca)  
[www.provideag.ca](http://www.provideag.ca)



# Vine Trimmer Type DE

## Standard equipment and extras



Collision protection at the rear, front and side. Aluminium clamping bar for easy re-tensioning of the fan belt and additional stabilization of the cutting unit.



Practical support trolley for easy attachment and detachment. No jacks or forklifts required.



Large blades and low rotational speed, as well as the 90mm fan belt pulley with cover, guarantee a significantly longer service life. No botrytis centrifuge and no turbo wear.



Easy to attach. No hoses on the bonnet.



A horizontal blade with fixed axle and separate oil motor ensures the greatest stability and longest service life. No guide rollers are necessary.



Wide adjustment range, for lanes from 160cm to approx. 250cm.

## Technical Data

- Cutting length: Horizontal 1 blade (70cm) with separate oil motor; vertical 3 blades (148/160cm) or 4 blades (176 cm)
- Three control units are required. Upon request joystick controller with double-acting cylinder for height adjustment, as well as separate width and tilt adjustment on the cutting units; in this case only one control unit required
- Operating pressure is approx. 50 bar at 10 litres/min
- High-grade steel