



# The New De-Leafer

Greater efficiency – thanks to newly designed bar rollers

Freilauber's patented de-leafer blows through the walls of foliage. The rows of leaves are caught by the rotating rollers. The leaves are plucked off in their entirety, meaning that the grapes are not damaged.

The fan speed and roller speed can be controlled independently of each other. The de-leafer can therefore be used from the flowering period right up to shortly before harvest. The de-leafer is also perfect for thinning out the foliage.



For further information visit [www.freilauber.de](http://www.freilauber.de),  
[www.provideag.ca](http://www.provideag.ca) or scan the QR-Code.

1.800.263.1287  
905.563.8261  
Beamsville, On, Canada

**PROVIDE** AGRO  
A BARTLETT COMPANY BARTLETT  
ESTABLISHED 1912

[info@provideag.ca](mailto:info@provideag.ca)  
[www.provideag.ca](http://www.provideag.ca)





### Important Facts

The pressure blower (new high-performance tangential fan) guides the bar rollers to the foliage, without coming into contact with it. This means:

- No soiling
- No cleaning
- Tractor and cooler remain clean
- Blower is not damaged by foreign objects or vibrations
- No cleaning elements
- Cleans inflorescence of flowerhoods
- Can be used irrespective of weather

Both pairs of bar rollers have their own drive motor. This means:

- No wear to the drive from friction
- No fan belts or spur wheels
- Leaves are plucked off in their entirety and not chopped
- Side shoots are clipped off and not pulled out

The de-leafer head boasts outstanding hydraulic adjustment possibilities

### Extras

- Controlled via a double-acting control unit or joystick control
- Hydraulically senses the walls of foliage
- Cutter bars

### Included with the product

- Mounting frame (also suitable for vine trimmers) with hydraulic tilt and double-acting height adjustment
- De-leafer with side offset and 180° swivel mechanism
- Support trolley and console
- Two double-acting control units (required on tractor)
- Collision protection fitted as standard
- Oil requirements one-sided de-leafer: 20 litres